



# PRODUCT SPECIFICATIONS

## DREAMGUARD PROTEX3

### DESCRIPTION

Liquid laminate for vinyl media and non water sensitive inks

### CONSTRUCTION

Water based

UV inhibitors to protect against yellowing and cracking

### AVAILABILITY

Three finishes: Satin, Matte and Gloss

1 pint sample, 1 gallon jug, 5 gallon bucket, 55 gallon drum

### PURPOSE

To protect textured vinyl wallcoverings from scratches, abrasion and stains

To help extend the original appearance of printed wallcoverings

Designed to be applied without the need for laminating machines

### APPLICATION

May be applied with paint roller or liquid laminating machinery

Milky white on application, dries clear in 1-2 hours

Use indoors, apply in temperatures between 55-85 degrees

Follow DreamGuard Application Instructions

### COVERAGE

800 to 1200 sqft./gal.

### ENVIRONMENTAL

Non-hazardous formulation, water based, MSDS available

Soap and water clean-up

Safe to ship, no VOC's

Safe for food contact when dry under FDA Regulations:

Code of Federal Regulations, Title 21, Food and Drugs

Part 175, Subpart A, Section 175.105

Part 175, Subpart A, Section 175.300

Part 176, Subpart B, Sections 176.170 & 176.180

### FLAMMABILITY

DreamGuard Protex3 is non-flammable in both a wet and dried state and will not support flame

Test method used: UL94 HB (horizontal burn test)

### COMMENTS

Keep from freezing.

\*Visit [www.hdwalls.com/specs](http://www.hdwalls.com/specs) for more information