



PRODUCT SPECIFICATIONS

TERRALON

DESCRIPTION

PVC free eco-friendly digitally printable wallcovering
Type II 54", 31% post consumer recycled content

CONSTRUCTION

100% Terralon™ (Proprietary Polyester/Natural Fiber Technology)

APPLICATION

Standard commercial wallcovering pastes/primers & techniques

PHYSICALS

Meets or exceeds federal spec CCCW-408D for Type II wallcoverings

ENVIRONMENTAL

PVC & POA (Olefin) free, no plasticizers, no phthalates, no formaldehyde, no chlorine, no halogen, no heavy metals, including: Cadmium, Mercury, Lead, or Zinc & no Ozone depleting chemicals
minimum of 31% post-consumer recycled content
Recycleable*

Breathable** very high permeability rating of 66 Perms based on ASTM E96 dry cup method
Made with 100% water based adhesive systems
No harmful off-gassing
Low VOC emitting

AIR QUALITY

Meets California Section IAQ1350 - third party certified by Berkley Analytical Associates

FLAME AND SMOKE

Class "A" fire rated - tested in accordance with ASTM-E84 Tunnel Test NFPA-101 (passed)

LEEDS ELIGIBILITY

Terralon™ can contribute towards the earning of 2 LEEDs credits and, conditionally, 2 others:

MR Credit 4.1 recycled content 20%

MR Credit 4.2 recycled content 30%

Conditionally:

MR Credit 2.1 contribution to project recycling program

MR Credit 2.2 contribution to project recycling program

MR credit 5.1 manufactured local to the new construction

EQ Credit 4.1 mounted with use of low emitting adhesives

**Permeable surface allows transfer of moisture to minimize possibility of mold & mildew growth. Terralon™ is intended for use in buildings that are properly designed & maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates.
Dry cup tests performed by VARTEST company.

*Visit www.hdwalls.com/specs for more information