



## PRODUCT SPECIFICATIONS

### VINYL WALLCOVERINGS

ARNETTE, ARTIST CANVAS, BEADS, CABRETTA  
CANVAS, LUSTER, MACHE, MATTE, MYSTICAL,  
PIQUE, PLASTER, PUEBLO, SANDBLAST, SUEDE

#### PHYSICAL PROPERTIES

Product Weight: 20 oz. per lineal yd., (13oz. per sq. yd.)

Vinyl Weight: 17 oz. per lineal yd.

Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.015 to 0.030 in.

\*depending on texture

Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven

\*depending on texture

#### BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp:

\*Exceeds Type II minimum of 50 lbs.

Cross Machine Direction-fill:

\*Exceeds Type II minimum of 55 lbs.

#### TEARING STRENGTH, SCALE

Machine Direction-warp:

\*Exceeds Type II minimum of 25lbs.

Cross Machine Direction-fill:

\*Exceeds Type II minimum of 25 lbs.

COLD CRACK RESISTANCE @ 20°F

No change

#### HEAT AGING (7 DAYS @ 158°F)

\*Does not become stiff, brittle, discolored, or show  
loss of grain

#### SPECIFICATIONS / TESTING / CERTIFICATION

Federal Specification:

\*CCC-408-D,C,B,A \*Type II \*Class A

CFFA Specification:

\*CFFA-W-101-D \*Type II \*Class A

#### FIRE TESTING

ASTM-E84 Tunnel Test Class A

NFPA286 Corner Burn Test Class A

NFPA265 Corner Burn Test Class A

BS476 Part 6&7

\*Meets or exceeds requirements for flame spread,  
smoke developments and flashover.

#### MOLD/MILDEW/BACTERIAL RESISTANCE

ASTM-G21 Specifications:

Passed all requirements of CCCW-408-D

#### ENVIRONMENT

NYC MEA: Register

\*Cadmium and Lead Free Formulation

\*Visit [www.hdwalls.com/specs](http://www.hdwalls.com/specs) for more information