



## PRODUCT SPECIFICATIONS

### VINYL WALLCOVERINGS

AMAMI / ARNETTE / ARTIST CANVAS / BEADS  
CABRETTA / CANVAS / LUSTER / MATTE / MYSTICAL  
PIQUE / PLASTER / PUEBLO / SATARA PEARL  
SATARTA STEEL / SILK / SUEDE

#### PHYSICAL PROPERTIES

Product Weight: 20 oz. per lineal yd., (13oz. per sq. yd.)

Vinyl Weight: 17 oz. per lineal yd.

Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.015 to 0.030 in.

\*depending on texture

Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven

\*depending on texture

#### BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp:

\*Exceeds Type II minimum of 50 lbs.

Cross Machine Direction-fill:

\*Exceeds Type II minimum of 55 lbs.

#### TEARING STRENGTH, SCALE

Machine Direction-warp:

\*Exceeds Type II minimum of 25lbs.

Cross Machine Direction-fill:

\*Exceeds Type II minimum of 25 lbs.

COLD CRACK RESISTANCE @ 20°F

No change

#### HEAT AGING (7 DAYS @ 158°F)

\*Does not become stiff, brittle, discolored, or show loss of grain

#### SPECIFICATIONS / TESTING / CERTIFICATION

Federal Specification:

\*CCC-408-D,C,B,A \*Type II \*Class A

Wa Specification:

W-101 Type II

#### FIRE TESTING

ASTM-E84 Tunnel Test Class A

NFPA286 Corner Burn Test Class A

NFPA265 Corner Burn Test Class A

EN15102 Class B

\*Meets or exceeds requirements for flame spread, smoke developments and flashover.

#### MOLD/MILDEW/BACTERIAL RESISTANCE

ASTM-G21 Specifications:

Passed all requirements of CCCW-408-D

#### ENVIRONMENT

Meets or exceeds EN12149 A,B,C - the EU Toxicity requirement for heavy metals (including Cadmium, Mercury, Lead and Antimony), and formaldehyde under EN15102

\*Visit [www.hdwalls.com/specs](http://www.hdwalls.com/specs) for more information