



PRODUCT SPECIFICATIONS

DURALON

DESCRIPTION

PVC Free, olefin-based vinyl alternative. TYPE II commercial strength. Duralon provides superior embossing depth and definition, and high level durability characteristics. Essentially, it is what you need without the parts you don't!

CONSTRUCTION

2-Ply Fabric Backed, TPO / Polyolefin Printable Face

APPLICATION

Standard commercial wallcovering pastes/primers & techniques. For indoor use in environmentally controlled spaces.

Availability

		US	Metric
	Widths:	54"	1.37m
	Lengths:	25yds, 50yds, 100yds	30m, 50m, 100m
Roll Sizes:	Rolls:	27"x15'	0.686m x 4.57m
	Weight:	20oz per lineal yd (13.3oz per sq yd)	457g/m ²
	Thickness:	0.017-0.027in. (depending texture)	0.432 to 0.686mm

Type II Properties

Passes for all criterion for WA 101 Type II properties, including:

Break Strength	Tear Strength	Cold Crack	Heat Aging
Shrinkage	Stain Resistance	Coating Adhesion (Bond)	Colorfastness
Washability	Scrubability	Blocking	Crocking

Specifications

CCC-408-D Type II	WA-101, NSF/ANSI 342 Sustainability Standard	NFPA Life Safety Code 101
DECLARE / RED LIST FREE	HPD / EPD available	LIVING BUILDING CHALLENGE

Fire Testing

ASTM E84 Tunnel Test	Passed Class A
EU Class Flame EN15102	Passed Class B, s2

Mold & Mildew

ASTM-G21

Environmental

PVC Free, No Plasticizers, No Pthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals. **Prop 65 Compliant. No Harmful Off Gassing. Low VOC Emitting.**

Air Quality

Meets California Section IAQ 1350 - Third Party certified by Berkeley Analytical Associates

Warranty

5 Year Warranty against manufacturing defects

*Visit www.hdwalls.com/specs for more information